



ABLE NEW ENERGY CO., LTD

ABLE Industrial Zone, Xintang Village
 GuanlanTown, Baoan District, Shenzhen, China 518110
 TEL:+86755-29807563 FAX:+86755-29807510



Lithium Manganese Dioxide Batteries (Li-MnO₂ batteries)

Type		Nominal Capacity	Nominal Voltage	Operating Current mA (max)		Standard Discharge Current mA	Cut Off Voltage	Dimension mm (max)		Weight	Operating Temperature
GB	IEC	mAh	V	Continuous	Pulse	mA	V	Dia.	Height	g	°C
2CR1/3N	2CR1/3N	160	6.0	50	80	2	2	11.8	10.8	3.3	-40~+60
CR1/3N	CR1/3N	160	3.0	50	80	2	4	12.0	25.2	8	-40~+60
CR14250	CR1/2AA	750	3.0	100	200	1	2	14.5	25	11	-40~+60
CR14335	CR2/3AA	1000	3.0	600	1000	10	2	14.5	33.5	13	-40~+60
CR14505	CR AA	1800	3.0	1000	2000	1	2	14.5	50.5	21	-40~+60
CR2	CR2	750	3.0	500	1000	10	2	15	27	11	-40~+60
CR17335	CR123A	1600	3.0	1000	2000	1	2	17	33.5	17	-40~+60
2CR5	2CR5	1600	6.0	1000	2000	20	4	34*17*45		38	-40~+60
CR-P2	CR-P2	1600	6.0	1000	2000	5	4	34.8*19.5*35.8		38	-40~+60
CR-V3	CR-V3	2900	3.0	2000	3000	1	2	28.6*14.6*52.2		39	-40~+60
CR17450	CR 4/5A	2200	3.0	1000	2000	1	2	17	45	25	-40~+60
CR17505	CR A	2300	3.0	1000	2000	1	2	17	50.5	28	-40~+60
CR26500	C	4500	3.0	1000	2000	25	2	26	50	55	-40~+60
CR34615	D	11000	3.0	1000	2000	10	2	34.2	61.5	110	-40~+60
Thin Cell		1200	3.0	800	1500	1	2	0.5*24*40		8	-40~+60
CR14250SE	1/2AA	850	3.0	7	70	1	2	14.5	25	11	-40~+60
CR14335SE	2/3AA	1300	3.0	8	80	0.5	2	14.5	33.5	16	-40~+60
CR14505SE	AA	1800	3.0	8	100	0.5	2	14.5	50.5	21	-40~+60
CR17335SE	2/3A	1800	3.0	8	100	1	2	17	33.5	20	-40~+60
CR17450SE	4/5A	2400	3.0	9	150	1	2	17	45	26	-40~+60
CR17505SE	A	2700	3.0	15	150	1	2	17	50.5	30	-40~+60
A9VP	9V	600	9.0	100	200	5	6	25.3*17.5*48.3		45	-40~+60
A9VL	9V	850	9.0	7	70	5	6	25.3*17.5*48.3		45	-40~+60
A9V	U9VL	1200	9.0	120	200	9	5.4	26.0*16.9*48.8		35	-40~+60

Note: Cells with suffix SE means bobbin construction.

The information contained herein is for reference only and does not constitute a warranty of performance.

ABLE New Energy Co.,Ltd
 ABLE Industrial Zone,Xintang Village,
 Guanlan Town,Baoan District,
 Shenzhen,China 518110
 Tel: +86 (0) 755 2980 7563
 Fax: +86 (0) 755 2980 7510
www.able-battery.com

All specifications subject to change without notice!